Serial No. 10/724809

Atty. Doc. No. 2002P19186US

## Amendments To the Claims:

Please amend the claims as shown.

1. (currently amended) A method for operating a gas turbine with a fossil-fuel fired combustion chamber comprising:

dividing exhaust gas exiting the gas turbine into a first and a second partial stream;

mixing the first partial stream with combustion air:

channeling the resulting mixture back to the combustion chamber; and

feeding the second partial stream to a carbon dioxide precipitation plant:

wherein the exhaust gas is cooled before being divided into the first and second partial stream and water forming during this process is removed;

wherein cooling of the exhaust gas takes place in at least a first and a second cooling stage; and

wherein the exhaust gas is channeled after exiting the gas turbine to a waste-heat steam generator for generating process steam for a steam turbine, then to the first cooling stage.

- 2. (canceled).
- 3. (canceled).
- 4. (canceled).
- 5. (currently amended) A method according to Claim 4claim 1, wherein the first cooling stage is operated by means of a coolant which is also used as a coolant of a condenser into which expanded steam exiting the steam turbine is introduced.
- 6. (previously presented) A method according to Claim 1, wherein the carbon dioxide precipitation plant incorporates a cooling process for cooling the second partial stream.
- 7. (previously presented) A method according to Claim 1, wherein carbon dioxide precipitated by the carbon dioxide precipitation plant is channeled to a storage facility.

NO. 7232 P. 5

Serial No. 10/724809

Atty. Doc. No. 2002P19186US

- 8. (currently amended) A method according to Claim 7, wherein the carbon dioxide is stored in a liquid and/or solid aggregate state; in particular a frozen state.
- 9. (currently amended) A device for operating a gas turbine with a fossil-fuel fired combustion chamber comprising:
- a branching device dividing exhaust gas exiting the gas turbine into a first and a second partial stream;
- a mixing device for mixing the first partial stream with combustion air and channeling the first partial resultant mixture stream to the combustion chamber; and
- a carbon dioxide precipitation plant adapted to be fed by the second partial stream; and
  a cooling device located upstream of the branching device to cool the exhaust gas and to
  remove water precipitated during this process, wherein the cooling device has at least a first and
  a second cooling stage; and a waste-heat steam generator located downstream of the gas turbine
  and upstream of the first cooling stage adapted to generate process steam for a steam turbine.
- 10. (canceled).
- 11. (canceled).
- 12. (canceled).
- 13. (currently amended) A device according to Claim 122, further comprising: a condenser located downstream of the steam turbine, the first cooling stage being capable of being operated by a coolant which is also used as a coolant of the condenser.
- 14. (previously presented) A device according to Claims 9, wherein the carbon dioxide precipitation plant is embodied as a refrigeration plant to cool the second partial stream.
- 15. (previously presented) A device according to Claims 9, further comprising: a storage facility in which carbon dioxide precipitated by the carbon dioxide precipitation plant can be stored.

JUL. 5. 2007 1:03PM 407-736-6440 NO. 7232 P. 6

Serial No. 10/724809

Atty. Doc. No. 2002P19186US

16. (currently amended) A device according to Claim 15, wherein the storage facility is embodied for storing at least one of the group of liquid and/or and solid carbon dioxide.

- 17. (currently amended) A method according to Claim 21, wherein the carbon dioxide precipitation plant incorporates a cooling process for cooling the second partial stream.
- 18. (currently amended) A method according to Claim 21, wherein carbon dioxide precipitated by the carbon dioxide precipitation plant is channeled to a storage facility.
- 19. (previously presented) A device according to Claim 16, wherein the storage facility is embodied for storing frozen carbon dioxide.
- 20. (currently amended) A device according to Claim 102, wherein the carbon dioxide precipitation plant is embodied as a refrigeration plant to cool the second partial stream.